


ELF 38" Ceiling Fan
FR-W1802-38L

MODERN FORMS
SMART FANS



PRODUCT DESCRIPTION

From bedrooms to boardrooms, pool houses to patios, Elf works its magic with a compact design that looks great anywhere- even outside. We make all our smart fans wet-rated- that means highly durable materials and weather-resistant finishes- so you can keep a consistent look and feel throughout your décor. Control your smart fan with the exclusive Modern Forms app, which integrates easily with smart devices you already own- if you want to turn it on, all you have to do is ask.

SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 13° Pitch, 38" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 15 lbs
- Total Power:** 63.5W
- Standards:** ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not available
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

- Light Source:** LED
- Light Wattage:** 23.5W
- Dimming:** Integrated
- Color Temperature:** 3000K (2700K / 3500K options available)
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

- Airflow:** 5257 cubic ft per minute on high
- Power:** 40 watts on high
- Airflow Efficiency:** 132 cubic ft per minute per watt
- Revolutions Per Minute:** 247 RPMs on high

WIRELESS PERFORMANCE

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1802-38L	2041	949	BZ <i>Bronze</i>	<i>Bronze</i>
			MW <i>Matte White</i>	<i>Matte White</i>
			TT <i>Titanium Silver</i>	<i>Titanium Silver</i>

Example: **FR-W1802-38L-BZ**

For 2700K add "-27"; 3500K add "-35" before the finish: **FR-W1802-38L-27-MW**

*Results may vary based on application and surroundings.



modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122






Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

ELF 38" Ceiling Fan

FR-W1802-38L

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

<p>RF Wall Control</p>  <p>F-WC</p>	<p>WT White</p>	<p>Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.</p>
<p>RF Remote Control</p> <p>F-RC</p>	<p>WT White</p>	<p>Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.</p>
<p>Wi-Fi Touch Panel Wall Control</p>  <p>F-TS</p>	<p>BK Black WT White</p>	<p>Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.</p>
<p>Downrod</p>  <p>XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in</p>	<p>AS Automotive Silver BA Brushed Aluminum BZ Bronze CFI Carbon Fiber** DW Dark Walnut</p>	<p>All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p>  <p>XF-I</p>	<p>GB Gloss Black GH Graphite GW Gloss White KO Koa†</p>	<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p>  <p>XF-SCK</p>	<p>MB Matte Black Matte MW White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver</p>	<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com	Headquarters/Eastern Distribution Center	Central Distribution Center	Western Distribution Center
Phone (866) 810.6615	44 Harbor Park Drive	1600 Distribution Ct	1750 Archibald Avenue
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Ontario, CA 91760