



**SIGNATURE SERIES SHALLOW DEPTH
18" DEPTH BEVERAGE CENTER**



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
HH24BS-4-1R/L	Indoor Shallow Depth Beverage Center Solid Stainless Steel Door
HH24BS-4-2R/L	Indoor Shallow Depth Beverage Center Solid Panel Ready Door
HH24BS-4-3R/L	Indoor Shallow Depth Beverage Center Stainless Steel Glass Door
HH24BS-4-4R/L	Indoor Shallow Depth Beverage Center Panel Ready Glass Door
HH24BO-4-1R/L	Outdoor Shallow Depth Beverage Center Solid Stainless Steel Door
HH24BO-4-2R/L	Outdoor Shallow Depth Beverage Center Solid Panel Ready Door
HH24BO-4-3R/L	Outdoor Shallow Depth Beverage Center Stainless Steel Glass Door
HH24BO-4-4R/L	Outdoor Shallow Depth Beverage Center Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- Industry exclusive 18" shallow depth for ultimate design flexibility in tight spaces
- Industry's largest selection of ADA compliant models for accessible and aging in place designs
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors

Quick Features:

- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (outdoor models only)
- Wine and refrigerator shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time
- Industry's best full 6 year warranty for owner ease of mind
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero global warming potential
- Storage for up to 41 cans and 10 bottles of wine



**SIGNATURE SERIES SHALLOW DEPTH
18" DEPTH BEVERAGE CENTER**

MODEL NUMBERS		HH24BS	HH24BO
MODEL DESCRIPTION		18" Indoor Beverage Center	18" Outdoor Beverage Center
ATTRIBUTES			
Perlick Anti-Condensation System		NO	YES
Energy Star Certified		YES	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)	23-7/8" (606 mm.)
	Depth - in. (mm)	18" (457 mm.)	18" (457 mm.)
	Height - in. (mm)	32" (813 mm.)	32" (813 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Depth - in. (mm)	18" (457 mm.)	18" (457 mm.)
	Height - in. (mm)	32-1/4" (819 mm.)	32-1/4" (819 mm.)
INTERNAL VOLUME Net. Cu. Ft. (L)		3.1 cu. ft.	3.1 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		185 lbs (83.91 kg.)	185 lbs (83.91 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps	2.2 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a(50g)	R600a(50g)
	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F (C)	33° (0.5) - 48° (8.8) Factory Set Point 36°(2.2°)	33° (0.5) - 48° (8.8) Factory Set Point 36°(2.2°)
	Heat Rejection (at 75°F)	350 BTU/hr	350 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes
PLUMBING		None Required	None Required

Installation Notes: To achieve 24" install depth, you must recess the outlet 7/8" into the wall directly behind the unit, or place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67992-L/R	Stacking Kit for HH24 models
67115-24	Wood Faces for Wine Shelves (7/pk)
67360	6" Toe Kick and Riser

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com



**SIGNATURE SERIES SHALLOW DEPTH
18" DEPTH BEVERAGE CENTER**

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HH24BS-4-1L	HH24BS4C-00-SLF0B	Left	No
HH24BS-4-1R	HH24BS4C-00-SRF0B	Right	No
HH24BS-4-2L	HH24BS4C-00-PL00B	Left	No
HH24BS-4-2R	HH24BS4C-00-PR00B	Right	No
HH24BS-4-3L	HH24BS4C-00-TLF0B	Left	No
HH24BS-4-3R	HH24BS4C-00-TRF0B	Right	No
HH24BS-4-4L	HH24BS4C-00-RL00B	Left	No
HH24BS-4-4R	HH24BS4C-00-RR00B	Right	No
HH24BS-4-1LL	HH24BS4C-00-SLFLB	Left	Yes
HH24BS-4-1RL	HH24BS4C-00-SRFLB	Right	Yes
HH24BS-4-2LL	HH24BS4C-00-PL0LB	Left	Yes
HH24BS-4-2RL	HH24BS4C-00-PR0LB	Right	Yes
HH24BS-4-3LL	HH24BS4C-00-TLFLB	Left	Yes
HH24BS-4-3RL	HH24BS4C-00-TRFLB	Right	Yes
HH24BS-4-4LL	HH24BS4C-00-RL0LB	Left	Yes
HH24BS-4-4RL	HH24BS4C-00-RR0LB	Right	Yes
HH24BO-4-1L	HH24BO4C-00-SLF0B	Left	No
HH24BO-4-1R	HH24BO4C-00-SRF0B	Right	No
HH24BO-4-2L	HH24BO4C-00-PL00B	Left	No
HH24BO-4-2R	HH24BO4C-00-PR00B	Right	No
HH24BO-4-3L	HH24BO4C-00-TLF0B	Left	No
HH24BO-4-3R	HH24BO4C-00-TRF0B	Right	No
HH24BO-4-4L	HH24BO4C-00-RL00B	Left	No
HH24BO-4-4R	HH24BO4C-00-RR00B	Right	No
HH24BO-4-1LL	HH24BO4C-00-SLFLB	Left	Yes
HH24BO-4-1RL	HH24BO4C-00-SRFLB	Right	Yes
HH24BO-4-2LL	HH24BO4C-00-PL0LB	Left	Yes
HH24BO-4-2RL	HH24BO4C-00-PR0LB	Right	Yes
HH24BO-4-3LL	HH24BO4C-00-TLFLB	Left	Yes
HH24BO-4-3RL	HH24BO4C-00-TRFLB	Right	Yes
HH24BO-4-4LL	HH24BO4C-00-RL0LB	Left	Yes
HH24BO-4-4RL	HH24BO4C-00-RR0LB	Right	Yes



SIGNATURE SERIES SHALLOW DEPTH
18" DEPTH BEVERAGE CENTER

