


PRINCESS – model: DR-362

Crystal Collection: Beauty Spots™

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Beauty Spots™ series are low voltage surface mount fixtures designed for use in drywall ceilings, grid ceilings, walls, or displays. Clear shades fit over the lamp and are retained by a spring band.

FEATURES

- Sold as complete unit - housing and trim
- Use 12V/24V remote electronic (order separately)
- Easily mounted on suspended or finished ceilings.
- Can be used individually as accent pieces or grouped together.
- LED and Xenon versions are dimmable with ELV dimmers
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Canopy faceplate is plated chrome. Wiring compartment is steel, painted black.

Light Source: LED 4.3W or Xenon Bi-Pin 20W

Mounting: No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface. 2 3/8" cut out hole.


Mounting: Integral wiring compartment with standard size knock out hole on top. When using a class II power supply, side hole may be used for wire entry

Dimming: ELV Dimming: 100%-10%

Standards: UL & cUL Listed.

Integral LED

* Dimming is not recommended



DR-362LED-CL/CH Princess

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	150	24V	4.5 W	50,000 hours	Clear / Chrome	2 3/8"


Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
120V	24V, 60W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	12 per transformer	30'
120V	24V, 96W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	21 per transformer	40'

Remote Transformer for Integral LED

EN-2460-RB2
EN-24100-RB2

12V Xenon Bi-Pin

* Dimmable with compatible dimmer match to power supply



DR-362-CL/CH Princess

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	200	12V, 24V	20 W	10,000 hours	Clear/ Chrome	2 3/8"

Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
120V	12V, 60W (class 2)	1W	6 5/8" x 1 5/8" x 1 1/8"	3	25'
120V	12V, 100W	1W	6 1/4" x 3" x 1 5/8"	5	30'
120V	12V, 150W	1W	6 1/4" x 3" x 1 5/8"	7	35'

Remote Transformer for Xenon Bi-pin

EN-1260-RB2
EN-12100-RB-AR
EN-12150-RB-AR

WAC Lighting

www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585