WAC LIGHTING




Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Die cast aluminum factory sealed housings with patent pending design for a water and dust proof IP66 rated outdoor luminaire

FEATURES

- Factory-Sealed LED Light Engine
- Die-cast aluminum construction
- Photo/Motion Sensor Compatible (Sold Separately)
- 120V Direct Wire No Driver Needed
- 85 CRI
- 39,000 hour rated life


SPECIFICATIONS

Construction: Die-cast aluminum **Power:** Line Voltage input (120V)

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Black, Bronze, White and Graphite **Standards:** IP66, Wet Location, ETL & cETL Listed **Operating Temperature:** -40°C (-40°F) to 40°C (104°F)

PHOTOMETRY



ORDER NUMBER

Model		Wattage	Comparable	Color temp		Delivered Lumens	Finish		
WP-LED415	Single	15W	75W	30 50	3000K 5000K	965 1030	aBK aBZ aGH aWT	Architectural Black Architectural Bronze Architectural graphite Architectural White	

Example: WP-LED415-30-aWT

DOUBLE SPOT Endurance

WP-LED430



MOTION SENSOR (120V) available in 3 complementary colors

PHOTOSENSOR (120V) available in 3 complementary colors











PC-120-BZ Bronze
PC-120-GY Gray
PC-120-WT White

